

KillTest

품질은 좋고 서비스도 더욱 좋습니다



덤프

<http://www.killtest.kr>

우리는 고객에게 년 동안 무상업데이트 서비스를 제공합니다

Exam : **300-360**

Title : Designing Cisco Wireless
Enterprise Networks

Version : DEMO

1.Which two types of information must be included in the installation inventory portion of the post-installation report? (Choose two.)

- A. all AP, controller, and MSE administrator credentials
- B. the names, locations, IP addresses, MAC addresses, etc. for every AP, controller, and MSE in the WLAN
- C. a layout of the rack that the equipment is installed
- D. results of the coverage audit performed with the site survey mapping tool
- E. the number and type of all WLAN clients and tags

Answer: AB

2.A customer wants to implement a wireless network in a historic location, but is concerned about the structural and aesthetic impact to the facility.

Which benefit of using wireless mesh addresses these concerns?

- A. PoE is required only at the installation location.
- B. The APs do not have LED lights.
- C. More wireless channels can be supported.
- D. APs do not need network connections.

Answer: A

3.An engineer is preparing for an indoor wireless LAN survey and is provisioning a survey kit.

Which three pieces of equipment should be included? (Choose three.)

- A. external connector access point
- B. integrated antenna access point
- C. coax low-loss cable
- D. battery operated power supply
- E. range finder
- F. Yagi antennas

Answer: BDE

4.Which three options are benefits of U-APSD? (Choose three.)

- A. optimized power-save mode periods
- B. increased call capacity
- C. bandwidth reservation
- D. synchronization of the transmission and reception of voice frames
- E. efficient roaming
- F. priority bandwidth and polling

Answer: ABD

Explanation:

Unscheduled automatic power-save delivery (U-APSD) is a feature that has two key benefits:

- The primary benefit of U-APSD is that it allows the voice client to synchronize the transmission and reception of voice frames with the AP, thereby allowing the client to go into power-save mode between the transmission/reception of each voice frame tuple. The WLAN client frame transmission in the access categories supporting U-APSD triggers the AP to send any data frames queued for that WLAN client in that AC. A U-APSD client remains listening to the AP until it receives a frame from the AP with an

end-of-service period (EOSP) bit set. This tells the client that it can now go back into its power-save mode. This triggering mechanism is considered a more efficient use of client power than the regular listening for beacons method, at a period controlled by the delivery traffic indication map (DTIM) interval, because the latency and jitter requirements of voice are such that a WVoIP client would either not be in power-save mode during a call, resulting in reduced talk times, or would use a short DTIM interval, resulting in reduced standby times. The use of U-APSD allows the use of long DTIM intervals to maximize standby time without sacrificing call quality. The U-APSD feature can be applied individually across access categories, allowing U-APSD can be applied to the voice ACs in the AP, but the other ACs still use the standard power save feature.

- The secondary benefit of this feature is increased call capacity. The coupling of transmission buffered data frames from the AP with the triggering data frame from the WLAN client allows the frames from the AP to be sent without the accompanying interframe spacing and random backoff, thereby reducing the contention experience by call.

Reference: http://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Mobility/vowlan/41dg/vowlan41dg-book/vowlan_ch2.html#wp1045982

5.A customer has restricted the AP and antenna combinations for a design to be limited to one model integrated antenna AP for carpeted spaces and one model external antenna AP, with high gain antennas for industrial, maintenance, or storage areas. When moving between a carpeted area to an industrial area, the engineer forgets to change survey devices and surveys several APs.

Which option is the best to reduce the negative impact of the design?

- A. Deploy the specified access points per area type.
- B. Resurvey and adjust the design.
- C. Increase the Tx power on incorrectly surveyed access points.
- D. Deploy unsurveyed access points to the design.

Answer: B