KillTest

품질은 좋고 서비스도 더욱 좋습니다



덤프

http://www.killtest.kr

우리는 고객에게 년동안 무상업데이트 서비스를 제공합니다

Exam: 300-430

Title: Implementing Cisco

Enterprise Wireless

Networks (ENWLSI)

Version: DEMO

- 1.On a branch office deployment, it has been noted that if the FlexConnect AP is in standalone mode and loses connection to the WLC, all clients are disconnected, and the SSID is no longer advertised.
- Considering that FlexConnect local switching is enabled, which setting is causing this behavior?
- A. ISE NAC is enabled
- B. 802.11r Fast Transition is enabled
- C. Client Exclusion is enabled
- D. FlexConnect Local Auth is disabled

Answer:D

2.An engineer must implement intrusion protection on the WLAN. The AP coverage is adequate and on-channel attacks are the primary concern. The building is historic, which makes adding APs difficult.

Which AP mode and submode must be implemented?

A. AP mode: local, AP submode: none
B. AP mode: monitor, AP submode: WIPS
C. AP mode: monitor, AP submode: none
D. AP mode: local, AP submode: WIPS

Answer:B

3.An engineer is implementing a FlexConnect group for access points at a remote location using local switching but central DHCP.

Which client feature becomes available only if this configuration is changed?

- A. multicast
- B. static IP
- C. fast roaming
- D. mDNS

Answer:A

- 4.A FlexConnect remote office deployment is using five 2702i APs indoors and two 1532i APs outdoors. When a code upgrade is performed and FlexConnect Smart AP Image Upgrade is leveraged, but no FlexConnect Master AP has been configured, how many image transfers between the WLC and APs will occur?
- A. 1
- B. 2
- C. 5
- D. 7

Answer:B

- 5. Where is a Cisco OEAP enabled on a Cisco Catalyst 9800 Series Wireless Controller?
- A. RF Profile
- B. Flex Profile
- C. Policy Profile
- D. AP Join Profile

Answer:B