

KillTest

높은 품질, 더 나은 서비스



연습 문제

<https://www.killtest.kr>

1년간 무료 업데이트 제공

Exam : C2090-317

**Title : DB2 11 System
Administrator for z/OS**

Version : DEMO

1. In complex DB2 recovery scenarios, it is important to understand the scope of which objects require recovery.

Which DB2 utility provides a list of the names of all table spaces in the table space set that is specified and a list of all the tables in those table spaces?

- A. CHECK
- B. REPORT
- C. QUIESCE
- D. RECOVER

Answer: D

Reference: http://www01.ibm.com/support/knowledgecenter/SSEPEK_10.0.0/com.ibm.db2z10.doc.ugref/src/tpc/db2z_re portsyntax.dita

2. The -ALTER UTILITY command changes the values of certain parameters of a utility.

Which two utilities can this command be issued against?

- A. COPY
- B. REORG
- C. MODIFY
- D. REBUILD
- E. RECOVER

Answer: B,D

Reference: http://www01.ibm.com/support/knowledgecenter/SSEPEK_11.0.0/com.ibm.db2z11.doc.admin/src/tpc/db2z_monitronlineutilities.dita

3. You execute the following SQL against the CDB (Communications Database) of your DB2 INSERT INTO SYSIBM.IPNAMES

```
(UNKNAM.SECURITY_OUT.USERNAMES,IBMREQD.IPADDR) VALUES ('REMOTEDB', 'P\ 'O'. 'N', *123.34.45.56');
```

```
INSERT INTO SYSIBM.IPLIST (LINKNAMEJPADDRJBMREQD) VALUES ('REMOTEDB', '123.34.45.56', *N');
```

```
INSERT INTO SYSIBM.IPLIST (LINKNAMEJPADDRJBMREQD) VALUES C REMOTEDB', '123.34.45.57', 'N');
```

```
INSERT INTO SYSIBM.USERNAMES
```

```
(TYPE,AUTHID.LINKNAME,NEWAUTHID.PASSWORD,IBMREQD) VALUES (T, 'USER1'. 'USER2\ ", ,PWD2,1 *N');
```

```
INSERT INTO SYSIBM.USERNAMES
```

```
(TYPE,AUTHID.LINKNAME,NEWAUTHID.PASSWORDJBMREQD) VALUES ('O', 'USER1'. 'USER3', *, 'PWD3', 'N');
```

There is no trusted connection to REMOTEDB. USER1 issues a query addressing remote data source REMOTEDB on your DB2 subsystem.

Which authorization id will be used on the remote data source REMOTEDB?

- A. USER1
- B. USER2
- C. USER3
- D. USER4

Answer: A

4.Which combination of subsystem parameter values will enable connection pooling for idle distributed database access threads?

- A. Specify subsystem parameter CMTSTAT = ACTIVE and set CONDBAT = MAXDBAT.
- B. Specify subsystem parameter CMTSTAT = INACTIVE and set CONDBAT < MAXDBAT.
- C. Specify subsystem parameter CMTSTAT = ACTIVE and set CONDBAT > MAXDBAT.
- D. Specify subsystem parameter CMTSTAT = INACTIVE and set CONDBAT >MAXDBAT.

Answer: C

Reference:<http://db2onlinehandbook.com/?p=1263>

5.You wish to set the threshold at which data in the class castout queue is cast out to disk for group buffer pool GBP10. You want the threshold to be 1000 pages.

Which parameter setting in the command -ALTER GBPOOL(GBP10) will accomplish this?

- A. GBPOOLT(10)
- B. CLASST(0.1000)
- C. CLASST(10.1000)
- D. GBPCHKPT(1000)

Answer: A

6.Which action should you take to improve the performance of authorization checking for stored procedures or user-defined functions?

- A. Set subsystem parameter EXTSEC to YES.
- B. Increase the value of subsystem parameter SECQTY.
- C. Increase the value of subsystem parameter AUTHCACH.
- D. Increase the value of subsystem parameter CACHERAC.

Answer: D

Reference:<http://www.redbooks.ibm.com/redbooks/pdfs/sg247134.pdf>(page 336)

7.You want to temporarily switch-off one of your trusted contexts.

- A. DROP TRUSTED CONTEXT...
- B. -STOP DB(DSNDB06) TS(SYSCONTX)
- C. ALTER TRUSTED CONTEXT ... DISABLE
- D. -STOP TRACE(AUDIT) AUDTPLCY(TRUSTED_CONTEXT)

Answer: C

8.Your database administrators plan to start using XML and they plan to have the XML documents being validated using type modifiers.

You must make sure that they are able to make XSR schemas available for this.

Which stored procedure(s), if any, must at least be created and functioning for that?

- A. XSR_REGISTER
- B. XSR_REGISTER, XSR_COMPLETE
- C. No stored procedures need to be created.
- D. XSRREGISTER. XSRCOMPLETE. XSRADDSCHMADOC

Answer: B

9.A column mask is defined on TB_A. Which statement runs successfully?

- A. SELECT ' FROM TB_A UNION ALL SELECT ' FROM TB_B
- B. SELECT ' FROM TB_A INTERSECT SELECT * FROM TB_B
- C. SELECT ' FROM TB_A EXCEPT ALL SELECT ' FROM TB_B
- D. SELECT'FROM TB A INTERSECT ALL SELECT * FROM TBB

Answer: A

10.Which subsystem parameter setting allows connection queuing?

- A. IDTHTOIN>0
- B. CONDBAT>0
- C. POOLINAC>0
- D. MAXCONGN > 0

Answer: D

Reference:http://www01.ibm.com/support/knowledgecenter/SSEPEK_10.0.0/com.ibm.db2z10.doc.inst/src/tpc/db2z_zpa_rmnotonpanels.dita(see MAXCONQN)