

KillTest

높은 품질, 더 나은 서비스



연습 문제

<https://www.killtest.kr>

1년간 무료 업데이트 제공

Exam : HP0-662

Title : NonStop Configuration and Planning

Version : DEMO

1. Assuming no I/O enclosures, how many electrical branch circuits are needed to provide power fault tolerance for a six-processor S7x000 system?

- A. 2
- B. 3
- C. 4
- D. 6

Answer: D

2. Which items would you expect to see on a network topology diagram? Select TWO.

- A. tape devices
- B. IP addresses
- C. routers
- D. disk mapping
- E. cable specifications

Answer: BC

3. What allows a customer to track open problem cases through the Web?

- A. Scout for NonStop servers
- B. Express Notice
- C. NonStop Technical Library (NTL)
- D. Total Web Support (TWS)

Answer: D

4. Which prediction is NOT produced by TCM?

- A. number of processors required
- B. number of logical disk volumes
- C. network response time
- D. processor and disk utilization

Answer: C

5. Which tool simplifies the task of migrating a database from many small disks to a smaller number of

large disks?

- A. MEDIACOM
- B. ASAP
- C. SMF
- D. MAPPER

Answer: C

6. DSM/SCM can be used to control customer software. Which program is used to prepare the software?

- A. CNFGINFO
- B. ZPHIRNM
- C. INITENV
- D. INITSTAT

Answer: A

7. To what type of adapter does a default configuration system console connect?

- A. E4SA
- B. MIOE
- C. FESA
- D. TRSA

Answer: B

8. Which process needs to be configured to ensure Expand connectivity between two systems?

- A. \$znet
- B. \$ncp
- C. \$expand
- D. \$zzatm

Answer: B

9. How many internal disk SCSI controllers are on a PMF CRU?

- A. 0
- B. 1
- C. 2
- D. 3

Answer: C

10. Which element is typically included in a separate document in response to a Request for Proposal (RFP)?

- A. software details
- B. timescales
- C. cost breakdown
- D. hardware details

Answer: C

11. Increasing the number of processors in a system _____.

- A. provides fault tolerance for the system consoles
- B. allows more disk units in group 1 of the system
- C. requires a cold load of the system
- D. allows more low-pin processes to run in the system

Answer: D

12. Which product can be used to project transaction growths into a resource upgrade timeline?

- A. GPA
- B. ASAP
- C. NSX
- D. TCM

Answer: D

13. What is the filename of the SCSI boot code for the G06.08 release?

- A. I1000

- B. IBOOT
- C. I2000
- D. ISCSI

Answer: B

14. Which utility is used for routine tape management operations?

- A. TAPECOM
- B. NSKCOM
- C. MEDIACOM
- D. TMFCOM

Answer: C

15. Which product requires a manual firmware update using TSM?

- A. FESA
- B. E4SA
- C. SWAN
- D. TRSA

Answer: C

16. Which tool has replaced Timbuktu for remote support?

- A. Timbuk3
- B. Remote Copy
- C. Carbon Copy
- D. PC Anywhere

Answer: C

17. What is a key difference between TSM low-level link and TSM service connection?

- A. service connection communicates only with the MSP
- B. service connection shows external devices
- C. service connection allows firmware updates

D. service connection allows system discovery

Answer: B

18. Which Windows NT services are required when configuring dial-out on TSM? Select TWO.

A. RPC

B. RAS

C. SAP Agent

D. Network Monitor Agent

E. SNMP

Answer: BE

19. In which volume and subvolume do the hardware configuration files reside?

A. \$system.system

B. \$system.sysnn

C. \$system.zsysconf

D. \$dsmscm.system

Answer: C

20. How can the ServerNet connectivity to CPU 5 be displayed in SCF?

A. INFO SERVERNET 5

B. STATUS SERVERNET \$ZSNET

C. INFO SERVERNET \$ZSNET

D. STATUS SERVERNET 5

Answer: B